



TANDBERG Compass MXP

Innovative, fully-integrated solution designed for public spaces. With simple controls, users can easily tap into resources such as information help desks, travel services and translation assistance.

DESIGN FEATURES

- Designed for use in public spaces
- Ease-of-use through a five button interface and simplified user menus
- Completely integrated system including camera, display, handset, speakers and microphone
- Built-in LED light source for improved video image quality
- Wall-mount design with a VESA 100 compliant interface
- Built in key lock to secure system

APPLICATION FEATURES

- View presentations and presenter simultaneously with DuoVideo and H.239 Dual Stream
- TANDBERG Expressway™ Technology
- Easy access to a custom directory for simple dialing

PERFORMANCE FEATURES

- Choice of Network: up to 384 kbps ISDN/768 kbps IP (H.323 or SIP)
- Superior video quality incorporating the H.264 standard
- Highest level of embedded encryption as well as IEEE 802.1x and H.235 authentication for security
- IPv6 support
- Protection against network interruptions with automatic Downspeeding and IPLR
- XGA LCD Screen

PROTECT YOUR TECHNOLOGY INVESTMENT WITH
TANDBERG'S PORTFOLIO OF **CONSTANT CARE SERVICES**.
VISIT WWW.TANDBERG.NET

UNIT DELIVERED COMPLETE WITH:

Built-in camera, microphone, speakers, cables,
12.1" LCD screen, LED light source, telephone handset,
wall-mount bracket

LCD SCREEN

Wide view angle screen
XGA resolution
Auto brightness

BANDWIDTH

H.320 up to 384 kbps
H.323 up to 768 kbps
SIP up to 768 kbps

FIREWALL TRAVERSAL

TANDBERG Expressway Technology™
Auto NAT
H.460.18, H.460.19 Firewall Traversal

VIDEO STANDARDS

H.261, H.263, H.263+, H.264

VIDEO FEATURES

Intelligent Video Management
Picture in Picture (PIP)
Dual Monitor Emulation (Side by Side)

VIDEO INPUTS (1 INPUT)

Built-in main camera
Extended Display Identification Data (EDID)

VIDEO FORMAT

NTSC, PAL, VGA, SVGA, XGA, or SXGA

LIVE VIDEO RESOLUTIONS

NATIVE NTSC:

400p (528 x 400 pixels) receive only
4SIF (704 x 480 pixels), Digital Clarity
Interlaced SIF (iSIF 352 x 480 pixels), Natural Video
SIF (352 x 288 pixels)

NATIVE PAL:

448p (576 x 448 pixels) receive only
4CIF (704 x 576 pixels), Digital Clarity
Interlaced CIF (iCIF 352 x 576 pixels), Natural Video
CIF (352 x 288 pixels)
QCIF (176 x 144 pixels) SQCIF (128 x 96 pixels) decode only

NATIVE PC RESOLUTIONS:

XGA (1024 x 768 pixels)
SVGA (800 x 600 pixels)
VGA (640 x 480 pixels)

WIDE RESOLUTIONS:

w288p (512 x 288 pixels) receive only
w448p (768 x 448 pixels) receive only
w720p (1280 x 720 pixels) receive only

STILL IMAGE TRANSFER

CIF, SIF, 4CIF (H.261 Annex D), 4SIF, VGA, SVGA, XGA

AUDIO STANDARDS

G.711, G.722, G.722.1, G.728, 64 bit MPEG4 AAC-LD

AUDIO FEATURES

CD-Quality 20KHz Mono
Automatic noise reduction
Acoustic echo canceller
Automatic gain control
Packet loss management
Active lip synchronization
GSM/Blackberry interference audio feature

PRIVACY FEATURE

Armored telephone handset

FRAME RATES

30 frames per second @ 168 kbps and above

DUAL STREAM

DuoVideo
H.239 dual stream
Dynamic bandwidth adjustment (H.323)
Available on H.323 & H.320

NETWORK FEATURES

Auto H.320/H.323 dialing
SIP
Downspeeding
Programmable network profiles
Intelligent Call Management
Maximum call length timer
Automatic SPID and line number configuration
(National ISDN, GR-2941-CORE)
SoftMux

EMBEDDED ENCRYPTION

H.320 and H.323 point-to-point calls
Standards-based: H.233, H.234, H.235 v2&v3,
DES and AES
NIST-validated AES
NIST-validated DES
Automatic key generation and exchange
Supported in Dual Stream

IP NETWORK FEATURES

IEEE 802.1x/EAP Network Authentication
H.235 Gatekeeper Authentication
DNS lookup for service configuration
Differentiated Services (DiffServ)
Resource Reservation Protocol (RSVP)
IP precedence
IP type of service (ToS)
IP adaptive bandwidth management
(including flow control)
Auto gatekeeper discovery
Dynamic layout and lip-sync buffering
Intelligent Packet Loss Recovery (IPLR)
H.245 DTMF tones in H.323
Cisco CallManager integration using ECS
IP Address Conflict Warning
Date and Time support via NTP
Call Services

IPv6 NETWORK SUPPORT

Dual Stack IPv4 and IPv6 simultaneous support
Net service support on IPv6: Telnet, SSH, HTTP, HTTPS,
ftp, SNMP, DNS, NTP, DHCP
Media support on IPv6: H.323, SIP Streaming

SECURITY FEATURES

Management via HTTPS and SSH
IP Administration Password
Menu Administration Password
Dialing Access code
Streaming password
H.243 MCU Password
VNC password
SNMP security alerts
Disable IP services
MD-5 Challenge
Network settings protection
SIP Authentication via NTLM
SIP Authentication via Digest

NETWORK INTERFACES

3 x ISDN BRI (RJ-45), S-interface
1 x LAN/Ethernet (RJ-45) 10/100 Mbit
(LAN/DSL/cable modem)
1 x USB for future usage

ETHERNET/INTERNET/INTRANET CONNECTIVITY

TCP/IP, DHCP, ARP, FTP, Telnet, HTTP, HTTPS,
SOAP and XML, MD-5 Challenge
SNMP Enterprise Management
Internal web server
Internal streaming server

OTHER MAJOR STANDARDS SUPPORTED

H.231, H.233, H.234, H.235 v2&v3, H.239, H.241, H.243,
H.281, BONDING (ISO 13871), H.320, H.323, H.331
RFC 3261, RFC 2237, RFC 3264, RC 3311, RFC 3550, RFC
2032, RFC 2190, RFC 2429, RFC 3407

CAMERA

1/4" CCD
752(H) x 582(V) resolution
Lens: f=4mm F1:1.2
64° horizontal field of view
49° vertical field of view
Minimum illumination 5.0 lux (video output 50%, AGC on)

CLOSED CAPTIONING/TEXT CHAT

T.140 text chat available from Telnet,
Web and User Interface

PRESENTATIONS AND COLLABORATION

Natural Presenter Package including:
Digital Clarity & Native Formats
Dual Monitor Emulation (Side by Side)
Streaming compatible with Cisco IP/TV, Apple QuickTime®,
RealPlayer® v8 etc.

SYSTEM MANAGEMENT

Support for the TANDBERG Management Suite
Total management via embedded web server, SNMP
Telnet, SSH, FTP and SOAP
Remote software upload: via web server, ftp server or ISDN

DIRECTORY SERVICES

Support for Local directories (My Contacts), Corporate
Directory and Global Directory
Unlimited entries using Server directory* supporting LDAP
and H.350
Unlimited number for Corporate directory (through by TMS)
400 number global directory
200 number local directory
Directories in Local Languages

16 MENU LANGUAGES AVAILABLE

Arabic, Simplified Chinese, Traditional Chinese, English,
French, German, Italian, Japanese, Korean, Norwegian,
Portuguese, Russian, Spanish, Suomi, Swedish and Thai
Chinese, Korean and Japanese Input Method Editors
Import Custom Language through TMS

CUSTOMIZED WELCOME SCREEN AND COMPANY LOGO

Pictures JPEG (logo.jpg): Recommended maximum size is
704x576 for Welcome Screen and 352x288 for the other screens

POWER

Auto-sensing power supply
100-250 VAC, 50-60 Hz
36 Watts max.

OPERATING TEMPERATURE AND HUMIDITY

0° C to 35° C (32° F to 95° F) ambient temperature
10% to 90% Relative Humidity (RH)

STORAGE AND TRANSPORT TEMPERATURE

-20° C to 60° C (-4° F to 140° F) at RH 10-90%
(non-condensing)

APPROVALS

Directive 73/23/EEC (Low Voltage Directive)
– Standard EN 60950
Directive 89/336/EEC (EMC Directive)
– Standard EN 55022, Class B
– Standard EN 55024
– Standard EN 61000-3-2/-3-3
Directive 1999/5/EEC (R&TTE Directive)
– Standard TBR3
Approved according to and CAN/CSA C22.2 No. 60950-1
Complies with FCC15B Class B

UNIT DIMENSIONS

Height: 21.8"/55.4 cm
Width: 17.4"/44.0 cm
Depth: 4.3"/11.0 cm
Weight: 33.0 lbs/15.0 kg

**Requires TANDBERG Management Suite 9 or newer*

*All specifications subject to change without notice,
system specifics may vary.*

*All images in these materials are for representational
purposes only, actual products may differ.*

*TANDBERG and Expressway are registered trademarks or
trademarks of TANDBERG in the U.S. and other countries.*

All other trademarks are property of their respective owners.

MTBF PRODUCT RELIABILITY/MTBF

*The predicted reliability is expressed in the expected
random Mean Time Between Failures (MTBF) for the
electronic components based on the Power On Hours:
Power On Hours (POH) > 69 000 hours
Useful Life Cycle > 6 years
ISO 9001 certificate is available upon request*

TANDBERG

Compass MXP

TANDBERG WORLD HEADQUARTERS
Phillip Pedersens vei 20
1366 Lysaker, Norway
Tel: +47 67 125 125
Fax: +47 67 125 234
Video: +47 67 126 126
E-mail: tandberg@tandberg.net

200 Park Avenue, Suite 2005
New York, NY U.S.A. 10166
Tel: +1 212 692 6500
Tel: +1 800 538 2884 (toll free in the U.S.)
Fax: +1 212 692 6501
Video: +1 212 692 6535
E-mail: tandberg@tandbergusa.com

July 2006